

6

5

4

3

2

1

## REVISION


ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	B	UPDATED PER ECO-13914	10/07/2024	HBAKKE	GUTTADAURO

(2X .44  
[11.3])


PIN 1



P1  
DISPLAYPORT 2.0  
MALE  
CONNECTOR



## WIRE MAP



SHELL

DRAIN WIRE

SHELL

UL21118

5 TWISTED PAIR, INDIVIDUALLY SHIELDED, 28AWG  
4 COND. 28AWG STRANDED TINNED COPPER  
WITH OVERALL BRAID SHIELD  
JACKET: LOW SMOKE ZERO HALOGEN,  
DISPLAYPORT 2.0, BLACK

PIN 1

P2  
DISPLAYPORT 2.0  
MALE  
CONNECTOR



## NOTES:

- VOLTAGE TEST: DC 300V 10MS  
INSULATION RESISTANCE: 5.0M ohm/min.  
CONDUCTANCE RESISTANCE: 5.0 ohm/max.
- DUST CAPS INSTALLED AT SHIPPING. (NOT SHOWN)
- CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
- CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED.

## REGULATORY COMPLIANCE:

EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

6

5

4

3

2

1

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [ ] ARE MILLIMETERS		<div>L-com®</div> <div>an INFINIT® brand</div> <div>Website: <a href="http://www.L-com.com">www.L-com.com</a></div> <div>Phone: 1.800.341.5266   1.978.682.6936</div>		<div></div> <div>INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5</div>	
TOLERANCES:				SCALE	SHEET
<div>X = ±.2 [5]   FRACTIONS</div> <div>.XX = ±.02 [0.5]   ± 1/32</div> <div>.XXX = ±.005 [0.13]   ANGLES ± 1°</div>		NONE		1 OF 1	
CABLE LENGTH TOLERANCES:		DESCRIPTION  DISPLAYPORT 2.0 CABLE ASSEMBLY, M/M, LSZH, BLK			
≤12 [305] = +1 [25] / -0					
>12 [305] ≤ 60 [1524] = +2 [51] / -0					
>60 [1524] ≤ 120 [3048] = +4 [102] / -0					
>120 [3048] ≤ 300 [7620] = +6 [152] / -0					
>300 [7620] = +5% / -0					
ALL DIMENSIONS ARE FOR REFERENCE ONLY AND SUBJECT TO CHANGE WITHOUT NOTICE UN-DIMENSIONED/NON-CRITICAL FEATURES MAY VARY IN SIZE AND LOCATION COLORS MAY VARY					
SIZE	CAGE CODE	DRAWN BY	ITEM NO.		REV
A	43321	DFRISIELLO	DP20Z-MM-BLK		B