


REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
Α	INITIAL RELEASE	07/19/2022	GUTTADAURO





"P1" 3.5 FEMALE **AUDIO** 



## NOTES:

- 1. ELECTRICAL TEST:
  - a. 100% OPEN SHORT MIS-WIRE TEST.
  - b. CONTACT RESISTANCE: 5 OHM MAX.
  - c. INSULATION RESISTANCE: 5M OHM MIN.
  - d. HI-POT TEST: DC 300V/10ms.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS

## TOLERANCES:

.X = ±.2 [5.08] FRACTIONS  $.XX = \pm .02 [.51]$ ± 1/32 .XXX = ±.005 [.13] ANGLES ± 1°

## CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0

120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0

ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.



50 High Street, West Mill, 3rd Floor, Suite #30 North Andover, MA 01845 USA.

Phone: 1.800.341.5266 | 1.978.682.6936 Fax: 1.978.689.9484 Website: www.L-com.com

E-mail: CustomerService@L-com.com

L-COM GLOBAL CONNECTIVITY ALL RIGHTS RESERVED. SHEET SCALE N/A

THIRD-ANGLE PROJECTION

THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF

SIZE CAGE CODE DRAWN BY ITEM NO. REV Α 43321 DZINN USBC35MMAD Α

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.