

Rubber Duck Magnetic Mount with 5 ft 100 Cable SMA Plug



HMA6-SM05

Features

- 5 Foot, Cable Black Performance Low-Loss 100 Series
- Base Material Black ABS & Flame Rating UL94-HB
- Weight .13 lbs. (0.05 kg)
- Diameter 1.6" (40.6 mm), Height 1.5" (38 mm)
- RP-SMA Plug Connector

Applications

- Mobile RF Applications
- WLAN
- Public Safety
- Wi-Fi

Description

The HMA6-Series magnetic mount is well suited for use with RP-SMA Plug Rubber Duck type antennas. The magnetic base is suitable for fixing to vehicles* or other metal surfaces as well as sitting on a tabletop or shelf. The 5 ft. (1.5m) High Performance Low-Loss 100 Series cable allows the user to position the antenna away from any obstacles or interference. The cable is terminated with an SMA Plug connector.

*Installation Note: This mount is not intended for use outside moving vehicles, such as on a trunk lid or roof.

This antenna mount, as well as our wide selection of superior quality RF parts, ship same day. Contact our knowledgeable and friendly technical support and sales staff for your answers on antennas or other L-com products.

Available Rubber Duck Antennas for this Mount

HG2402RD-1-RSF 2.4 GHz 2.2 dBi

HG2403RD-1-RSF 2.4 GHz 3 dBi

HG2405RD-1-RSP 2.4 GHz 5.5 dBi

HG2407RD-1-RSP 2.4 GHz 7 dBi

HG2409RD-1-RSP 2.4 GHz 9 dBi

HG2458RD-1-RSP 2.4 GHz to 5.8GHz 3 dBi

HG1903RD-RSP 1.9 GHz 3 dBi

HG3505RD-RSP 3.5 GHz 5 dBi

HG903RD-RSP 900 MHz 3 dBi

HG905RD-1-RSP 900 MHz 5 dBi

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Rubber Duck Magnetic Mount with 5 ft 100 Cable SMA Plug HMA6-SM05](#)

Rubber Duck Magnetic Mount with 5 ft 100 Cable SMA Plug



HMA6-SM05

Configuration

Housing Material and Plating	Brass
------------------------------	-------

Mechanical Specifications

Housing Material	Brass
Size	
Length	1.6 in [40.64 mm]
Width	1.6 in [40.64 mm]
Height	1.7 in [43.18 mm]
Weight	1.4 lbs [635.03 g]

Environmental Specifications

Environmental Specification Notes:
-30°C to +60°C Operating Temperature

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Rubber Duck Magnetic Mount with 5 ft 100 Cable SMA Plug from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

T-Rev.D